

Commercial Products (Embedded)

Model Number	Description	Freq	Input Voltage	Form Factor (L x W x H)	AES 128-bit	AES 256-bit	Interface	Max Power Output	Antenna Connector	FCC / IC	ETSI	Class 1 Div 2	RoHS
GXM-T14	2.4-2.483 GHz, 153.6K Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level, TTL, 3.3-5.0 VDC, 14-Pin Data Connector, MMCX RF Connector, UL, ETSI	2.400 - 2.438 GHz	3.3 - 5	2" x 1.4" x .38"			TTL	500 mW	MMCX	✓	✓	✓	✓
GXM-T24	2.4-2.483 GHz, 153.6K Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level, TTL, 3.3-5.0 VDC, 24-Pin Data Connector, MMCX RF Connector, UL, ETSI	2.400 - 2.438 GHz	3.3 - 5	2" x 1.4" x .38"			TTL	500 mW	MMCX	✓	✓	✓	✓
GXM-MR-R	2.4-2.483 GHz, 153.6K Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level with interface board, RS232, 6-30VDC, with MMCX Connector, UL, ETSI	2.400 - 2.438 GHz	6 - 30	2.75" x 2.4" x .40"			RS232	500 mW	MMCX	✓	✓	✓	✓
GXM-MR-T	2.4-2.483 GHz, 153.6K Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level with interface board, TTL, 6-30VDC, with MMCX Connector, UL, ETSI	2.400 - 2.438 GHz	6 - 30	2.75" x 2.4" x .40"			TTL	500 mW	MMCX	✓	✓	✓	✓