

Govt., Export, and Militart-Only Products (Embedded)

Model Number	Description	Freq	Input Voltage	Form Factor (L x W x H)	AES 128-bit	AES 256-bit	Interface	Max Power Output	Antenna Connect or
MM2-M13-LV-C	1.3 GHz Spread Spectrum wireless data transceiver, RS232/RS485, Board level, 5 VDC		5	2" x 2" x .30"			RS232/ 422/ 485	1 Watt	MMCX
MM2-M13-LV-T	1.3 GHz Spread Spectrum wireless data transceiver, TTL, Board level, 5 VDC		5	2" x 2" x .30"			TTL	1 Watt	MMCX
MM2-M13-C	1.3 GHz Spread Spectrum wireless data transceiver, RS232/RS485, Board level, 8-30 VDC		8 - 30	2" x 2" x .30"			RS232/ 422/ 485	1 Watt	MMCX
MM2-M13-T	1.3 GHz Spread Spectrum wireless data transceiver, TTL, Board level, 8-30 VDC		8 - 30	2" x 2" x .30"			TTL	1 Watt	MMCX
MM2-M13-P	1.3 GHz Spread Spectrum wireless data transceiver, Ethernet, 2-RS232, Board level, 5 VDC		5	4" x 2" x .50"	✓		1 Ethernet + 2 RS232	1 Watt	MMCX