

Model Number	Description	Freq	Input Voltage	Form Factor (L x W x H)	AES 128-bit	AES 256-bit	Interface	Max Power Output	Antenna Connector
MM2-EX-T	902-928 MHz, 153.6 Kbps Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level, TTL, 5.0 VDC, with MMCX Connector. 1.5 W	902-928 MHz	5	2" x 1.4" x .38"			TTL	1.5 Watt	MMCX
MM2-EX-T-A1	902-928 MHz, 153.6 Kbps Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level, TTL, 5.0 VDC, with MMCX Connector. 1.5 W	902-928 MHz	5	2" x 1.4" x .38"	✓		TTL	1.5 Watt	MMCX
MM2-EX-T-A2	902-928 MHz, 153.6 Kbps Over the Air Data Rate, Spread Spectrum wireless data transceiver, Board level, TTL, 5.0 VDC, with MMCX Connector. 1.5 W	902-928 MHz	5	2" x 1.4" x .38"	✓	✓	TTL	1.5 Watt	MMCX
MM2-EX-P	902-928 MHz, 153.6kbps Over the Air Data Rate, Spread Spectrum wireless data transceiver, Ethernet, Board level, 5 VDC, with MMCX Connector, 1.5 W	902-928 MHz	5	4" x 2" x .50"			1 Ethernet + 2 RS232	1.5 Watt	MMCX